

## HBKO SS 765/100 Stainless Steel Hygienic Border Panel and Wall Protector on the Flooring

Description		nti-bacterial, dirt and stain-resistant, easy-to-clean Stainless Steel Hygienic Border Panel and Vall Protector.
Product Code		IBKOSS765100-00, HBKOSS765100-ID (internal corner), HBKOSS765100-DD (external corner), IBKOSS765100SSB (right-left end pieces)
Areas of Use	H Cl	ood Industry (Meat, Fish, Milk, Dairy Products, Bakery Products, Oil, Food, Beverage, etc.) lealthcare Industry (Hospitals, Laboratories, Pharmaceutical Manufacturing & Storage), chemicals, Petrochemicals, Automotive, Cosmetics, Logistics and Transportation, Tourism, chopping Centers and Supermarkets, etc.
Technical Specifications	B cc R	Bottom edges of walls; Radius rotation. (r = 47,5 mm. ~ $\emptyset$ 95 mm.) Bonded with a special technique using stainless visco concrete composite with stainless visco oncrete filling reinforced with iron of class AISI 304 and AISI 316 L. Besistant to oil, acids, cleaning chemicals, and medium and heavy impacts, complying with food ygiene. Usage temperature range: -40°C / +80°C
Fire Reaction Class	: N	lot flammable.
Material	: St	tainless hygienic composite bordure
Color	: St	tainless steel.
Installation	he	<b>As an adhesive;</b> VIBROSER H70 (Hybrid) MS Polymer based one-component adhesive with high ad- esion strength and ISEGA certification, appropriate for food and sanitation hygiene, and resistant o acid and chemicals, is used. (H70 600 ml. Sausage Consumption Average ~2,5 m. adhesive)
	a	<b>As joint filler;</b> S300 Neutral Silicone 300ml, which is suitable for food and health hygiene ind does not form mold and fungus on its surface, provides high heat resistance up to 300C. 600 ml. Sausage Average ~6 m. joint consumption)
Dimensions	: H	leight: 765 mm. Length: 1,000 mm. Thickness: 100 mm. Radius Diameter: [r = 47,5 mm. ~ $\emptyset$ 95 mm]
Weight		IBKOSS765100-00; ~176,000 kg/m. HBKOSS765100-ID internal corner ~49,000 kg/pc. HBKOSS765100-DD xternal corner ~38,000 kg/pc. HBKOSS765100SSB right-left end pieces ~19,000 kg/pc.
Packaging		roduct is shipped on pallets, within boxes or crates, depending on quantity, wrapped in nylon hrink packages in the form of single packs.
HROSS76510-D		

